

## **INSTALLATION NOTES:**

1) TYPICAL PIN/STAPLE INSTALLATION PATTERN SHOWN.

2) ADD PINS/STAPLES AS NEEDED TO PROVIDE INTIMATE CONTACT OF GRASSGUARD WITH GRADE.

3) PINS/STAPLES TO BE INSTALLED FLUSH WITH GRADE.

4) FILL SHALLOW DEPRESSIONS WITH FREE DRAINING (NON-CLAY) FILL PRIOR TO INSTALLATION OF GRASSGUARD.

5) WEAK AND/OR SATURATED SOILS MAY REQUIRE DRAINAGE IMPROVEMENT AND OR STABILIZATION PRIOR TO INSTALLATION.

6) SURFACE MUST BE REASONABLY LEVEL, FIRM AND FREE DRAINING.

7) IT IS NOT ADVISABLE TO FILL OR COVER GRASSGUARD WITH SOIL.

8) AS ROLLED PRODUCTS TEND TO HAVE "MEMORY", IT IS ADVISABLE TO UNROLL GRASSGUARD AND ALLOW AT LEAST ONE HOUR (OR MORE IN COLD CLIMATES) FOR THE MATERIAL TO REGAIN ITS NATURAL FLAT SHAPE.

9) DUE TO THE MANUFACTURING PROCESS, ONE SIDE OF GRASSGUARD WILL BE MORE ROUGH (COARSE.) THE SURFACE MUST BE INSPECTED PRIOR TO INSTALLATION TO VERIFY THE ROUGH SIDE IS INSTALLED FACE UP.

10) PRIOR TO FULL VEGETATED MATURITY, GRASSGUARD STRONGLY RECOMMENDS THAT ACCESSIBILITY BE DISCOURAGED OR DENIED, AND APPROPRIATE SLIP-HAZARD WARNING SIGNAGE BE ERECTED.

11) PIN AND STAPLE OPTIONS:

- A) 6" X 1" X 6" U-SHAPED STAPLE
- B) 8" X 1" X 8" U-SHAPED STAPLE
- C) 12" PIN WITH WASHER
- D) SOIL ANCHORS (PER THE DESIGN ENGINEER'S
- RECOMMENDATION)

12) DIMENSIONS OF GRASSGUARD SCOUR APRON TO BE PER DESIGN ENGINEER'S RECOMMENDATION.

13) GRASSGUARD SCOUR APRON TO BE INSTALLED DIRECTLY OVER A TRM (TURF REINFORCEMENT MAT) PER THE DESIGN ENGINEER'S RECOMMENDATION.

## **Grass Reinforcement Mesh** TYPICAL SCOUR PROTECTION INSTALLATION DETAIL

5-16